


Sophtech



Worldwide

Sophtech Worldwide


13131 Hamilton Commons Blvd

Fishers, Indiana 46037

Phone: 317-776-5680 Fax: 317-776-5687

www.sophtech.net

sales@sophtech.net



(Closed End Cap)

All dimensions in inches, +/- .010 unless otherwise specified.

This confidential drawing and the information contained herein is the sole property of Sophtech Worldwide and may not be used or reproduced in any manner without written consent.

STF10-0135 Series

Temperature Range: -45° to +225° with Nitrile Seals

-20° to +225° with Viton Seals


Hardware Material: Corrosion protected metal endcaps and core

Filter Medium: Inert Micro-Glass fibers impregnated with stable resin, supported by polymer mesh

Collapse Rating: 150 psid per ISO-2941

Removal Rating ISO 4572	
Grade	$\beta_x > 200$
1um	1
3um	3
6um	6
12um	12
25um	25

Removal Rating - ISO 16889						
Grade	um [©] Rating for Beta Value					
	2	10	75	100	200	1000
1um	<2	<2	<2	<2	2.0	2.5
3um	<2	<2	3.1	3.3	3.8	5
6um	2.1	3.4	5.0	5.2	5.7	7
12um	3.2	5.5	8.3	8.7	9.7	12
25um	7.2	11.0	15.8	16.5	18.2	22



Part Number Information	
STF10-0428B (Buna)	1um
STF10-0428V (Viton)	
STF10-0133B (Buna)	3um
STF10-0133V (Viton)	
STF10-0134B (Buna)	6um
STF10-0134V (Viton)	
STF10-0135B (Buna)	12um
STF10-0135V (Viton)	
STF10-0136B (Buna)	25um
STF10-0136V (Viton)	

Phone: 317-776-5680

Fax: 317-776-5687

Email: sales@sophtech.net