


Sophtech



Worldwide


Sophtech Worldwide

**13131 Hamilton Commons Blvd
Noblesville, Indiana 46060**

Phone: 317-776-5680 Fax: 317-776-5687


www.sophtech.net

sales@sophtech.net



STF10-0211 Series

- Temperature Range:** -45° to +225° with Nitrile Seals
-20° to +225° with Viton Seals
- Hardware Material:** Corrosion Protected metal endcaps and core
- Filter Medium:** Inert Micro-Glass fibers impregnated and bonded with stable resin, supported by polymer mesh
- Collapse Rating:** 150 psid per ISO-2941
- Removal Rating:** Beta 3 > 200
- Seals Available:** "219" O'Ring, SOB



GPM - 150 SUS, 0.9 SG Fluid
Pressure drop varies linearly with viscosity.

Grade	Removal Rating - ISO 16889					
	um© for Beta Value					
	2	10	75	100	200	1000
3um	<2	<2	3.1	3.3	3.8	5



All dimensions in inches, +/- .010 unless otherwise specified.

This confidential drawing and the information contained herein is the sole property of Sophtech Worldwide and may not be used or reproduced in any manner without written consent.

Filter Number Information	
STF10-0211B (Buna)	3um
STF10-0211V (Viton)	

Phone: 317-776-5680

Fax: 317-776-5687

Email: sales@sophtech.net