


**SophTech**



**Worldwide**

**SophTech Worldwide**

13131 Hamilton Commons Blvd  
Noblesville, Indiana 46060

Phone: 317-776-5680 Fax: 317-776-5687

[www.sophtech.net](http://www.sophtech.net)

[sales@sophtech.net](mailto:sales@sophtech.net)

**STF10-0413 Series**


**Temperature Range:** -45° to +225° with Nitrile Seals  
-20° to +250° with Viton Seals

**Hardware Material:** Corrosion protected metal endcaps and core


**Filter Medium:** Inert Micro-Glass fibers impregnated and bonded with stable resin, supported by polymer mesh

**Collapse Rating:** 150 psid per ISO-2941

**Removal Rating:** Beta 1 > 200 per ISO 4572



All dimensions in inches, +/- .010 unless otherwise specified.



GPM - 150 SUS, 0.9 SG Fluid  
Pressure drop varies linearly with viscosity.

Grade	Removal Rating - ISO 16889					
	um© for Beta Value					
	2	10	75	100	200	1000
1um	<2	<2	<2	<2	2	2.5



Filter Part Number Information	
STF10-0413B (Buna)	1um
STF10-0413V (Viton)	

This confidential drawing and the information contained herein is the sole property of SophTech Worldwide and may not be used or reproduced in any manner without written consent.